



# Design in the Shared Space Practice and Research



*Architect: WRNS / HDR*

**The Salk Institute – Jacobs Science and Technology Center**








# OPTIONS FOR EARTHQUAKE RESISTANT DESIGN

Design Decisions Have Measurable Consequences




**Structure** →  
25% of building value




75% of building value





# Two Halves





# The Base





An ACI Standard

Requirements for Design of a Special Unbonded Post-Tensioned Precast Shear Wall Satisfying ACI 550.6 (ACI 550.7) and Commentary

Reported by Innovation Task Group 5

# Design Basis




Fig. R6.2—Conditions as probable flexural strength for base of wall of Fig. R1.1(a).




Fig. R1.1(a)—Main features of uncoupled unbonded post-tensioned precast shear wall.

# Seismic Performance of Precast Reinforced and Prestressed Concrete Walls

Tony Holden<sup>1</sup>; Jose Restrepo<sup>2</sup>; and John B. Mander<sup>3</sup>

**Abstract:** Two geometrically identical half-scale precast concrete cantilever wall units were constructed and tested under quasi-static reversed cyclic lateral loading. One unit was a code compliant conventionally reinforced specimen, designed to emulate the behavior of a ductile cast-in-place concrete wall. The other unit was part of a precast partially prestressed system that incorporated post-tensioned unbonded carbon fiber tendons and steel fiber reinforced concrete. **Hysteretic energy dissipation devices** were provided in the latter unit **in the form of low yield strength tapered longitudinal reinforcement, acting as a fuse connection between the wall panel and the foundation beam.** The conventional precast reinforced wall performed very well in terms of the ductility capacity and energy absorption capability, reaching 2.5% drift before significant strength degradation occurred. The precast partially prestressed wall unit achieved drift levels well in excess of 3% with no visible damage to the wall panel prior to failure. Test results and performance comparisons between the precast partially prestressed wall system and the precast conventionally reinforced unit are presented.

DOI: 10.1061/(ASCE)0733-9445(2003)129:3(286)

CE Database keywords: Seismic stability; Walls; Concrete, reinforced; Concrete, precast.

## Introduction

The earthquake-structural engineers' role has historically focused on ensuring life safety while recognizing the limitations that economics places on design. To design a structure elastically using conventional design methods and philosophies has generally been considered impractical. Engineers, in general, have designed structures for reduced lateral forces and accepted damage in potential plastic hinge zones, which are specifically detailed for ductility. No other economic parameters, such as the cost of damage to equipment and stored goods and the cost associated with loss of operation following a moderate or strong earthquake, are currently accounted for in the design process.

One of the main disadvantages of conventional cast-in-place construction, or precast concrete construction designed to behave as "if monolithic," is that regions in the lateral force resisting system are likely to be sacrificed in moderate and strong earthquakes. Significant damage involving large residual lateral displacements and wide residual cracks is expected to occur with such systems; hence, the cost and consequences of damage after an earthquake can be significant to the building occupant. Uncoupling the energy dissipation mechanism from the structure is an ideal solution that was first conceived and implemented through

seismic isolation. This solution, however, has generally been restricted in the United States and New Zealand to nationally significant structures.

The excellent seismic performance of buildings constructed incorporating structural walls is well documented (Wood et al. 1987; Wyllie 1989; Fintel 1995). For example, during the 1988 Armenia earthquake poorly designed and constructed buildings that incorporated precast concrete walls as the main lateral force resisting system performed substantially better than buildings built with other structural systems (Wyllie 1989). Buildings where lateral force resistance was provided by structural walls also showed excellent performance during the 1985 Chilean earthquake (Wood et al. 1987).

Although structural walls are a common and cost-effective way of providing lateral force resistance to buildings in seismic areas of the world there has been a drive to make wall systems more economical. Historically, cast-in-place reinforced concrete has been the most commonly used method of construction for structural wall systems. More recently, there has been an increased use of precast concrete walls of either the tilt-slab or factory-built variety; their design being carried out to emulate the behavior of their cast-in-place counterparts.

Fig. 1 schematically compares the response of (a) a conventional reinforced concrete system; (b) a fully prestressed precast concrete system; and (c) a partially prestressed (hybrid) concrete system. For the last two prestressed wall systems the tendons, if left unbonded over a certain length, remain elastic during rocking. In this way the elastic restoring force will essentially prevent residual lateral displacements from occurring. Since the concrete is not bonded to the tendons, considerably less cracking is induced than in monolithic walls that rely solely on bonded reinforcement to provide the lateral force resistance. The behavior of such a system can be described as being **bilinear elastic.** In these systems **cosmetic damage is restricted to the bottom corners of the wall about which it rocks. By armoring the ends of a prestressed concrete wall with steel plates and embedding a mating steel plate in the foundation,** it is possible to avoid any damage,

<sup>1</sup>Project Engineer, KPFF Consulting Engineers, 180 Pacific Way, San Francisco, CA 94111.

<sup>2</sup>Associate Professor, Dept. of Structural Engineering, Univ. of California at San Diego, 9500 Gilman Dr., La Jolla, CA 92093-0085.

<sup>3</sup>Professor of Civil Engineering, Univ. of Canterbury, Private Bag, 4800, Christchurch, New Zealand.

Note. Associate Editor: Takeru Igusa. Discussion open until August 1, 2003. Separate discussions must be submitted for individual papers. To extend the closing date by one month, a written request must be filed with the ASCE Managing Editor. The manuscript for this paper was submitted for review and possible publication on November 6, 2001; approved on May 21, 2002. This paper is part of the *Journal of Structural Engineering*, Vol. 129, No. 3, March 1, 2003. ©ASCE, ISSN 0733-9445/2003/3-286-296/\$18.00.

## Shake-table test of a two-storey low-damage concrete wall building

Richard S. Henry<sup>1</sup> | Ying Zhou<sup>2</sup> | Yiqiu Lu<sup>1</sup> | Geoffrey W. Rodgers<sup>3</sup> | Anqi Gu<sup>2</sup> | Kenneth J. Elwood<sup>1</sup> | Tony Y. Yang<sup>4</sup>

<sup>1</sup>Department of Civil and Environmental Engineering, University of Auckland, Auckland, New Zealand

<sup>2</sup>College of Civil Engineering, Tongji University, Shanghai, China

<sup>3</sup>Department of Mechanical Engineering, University of Canterbury, Christchurch, New Zealand

<sup>4</sup>Department of Civil Engineering, University of British Columbia, Vancouver, British Columbia, Canada

### Correspondence

Yiqiu Lu, Department of Civil and Environmental Engineering, University of Auckland, 20 Symonds St Auckland Central, Auckland 1010, New Zealand.  
Email: yiqiu.lu@auckland.ac.nz

### Funding information

International Joint Research Laboratory of Earthquake Engineering; New Zealand Ministry of Business, Innovation and Employment; New Zealand center of earthquake resilience (QuakeCoRE); Concrete NZ



### Abstract

The increasing need to reduce damage and downtime in modern buildings has led to the development of a low-damage design philosophy, where the earthquake loads can be resisted with damage confined to easily replaceable components. Post-tensioned (PT) concrete walls have emerged as a popular low-damage structural system that have been implemented in a range of buildings. In order to provide essential evidence to support the development of low-damage concrete structures, a system-level shake-table test was conducted on a two-storey low-damage concrete wall building implementing state-of-art design concepts. **The test building included PT rocking walls that provide the primary lateral-load resistance in both directions, a frame that utilized slotted beam connections, and a range of alternative energy dissipation devices that were installed at wall base or/and beam-column joints.** The building was subjected to **39 tests** with a range of intensity ground motions, incorporating both unidirectional and bidirectional ground motions on the structure with different combinations of wall strength and energy dissipating devices. **The building performed exceptionally well** during the intense series of tests, confirming the suitability of both the design methods and the connection detailing implemented. The building **achieved an immediate occupancy performance objective** even when subjected to **maximum considered earthquake hazard shaking.** The building exhibited **only minor damage** at the conclusion of testing, with **distributed cracking in the floors and cosmetic spalling in the wall toes** that did not compromise structural capacity or integrity and could be easily repaired with minimal disruption. The test has provided a rich dataset that is available for further analysis of the building response and validation of design methods and numerical models.

### KEYWORDS


displacement-based design, energy dissipating device, low-damage design, post-tensioned wall, precast concrete, PRESS, repairability, rocking wall, seismic design, self-centering, shake-table test, slotted beam, system level, wall-to-floor













**10 SHEAR WALL INTERFACE**  
1" = 1'-0"





**9 SHEAR WALL INTERFACE**  
1" = 1'-0"




**NOTE:**  
MATERIAL PROPERTIES:  
-A572 Gr. 50  
-YIELD STRENGTH:  $F_y = 60-65$  ksi  
-TENSILE STRENGTH:  $F_u = 80$  ksi










# NLRHA w. OpenSees





From: Marriott, D.J., 2009. *The development of high-performance post-tensioned rocking systems for the seismic design of structures.*







# The Bridge










Lateral Displacements for Skylight & Operable Glass Window Wall:



Case 1:  
E-W displacement, together

Case 2:  
N-S displacement, together

Case 3:  
E-W displacement, separating

Case 4:  
N-S displacement, apart & together

Note:  
Consider E-W and N-S cases concurrently.  
I.e.,  
-Cases 1+2  
-Cases 1+4  
-Cases 2+3  
-Cases 3+4

Displacements (inches)				
Case	DBE Mean	DBE Max	MCE Mean	MCE Max
1	1.06	1.63	1.92	3.00
2	1.27	2.11	2.23	4.40
3*	1.51	2.31	2.72	4.25
4*	1.80	2.99	3.16	6.23

Recommended criteria:

At **DBE Mean** displacements:

- no structural damage to glazing systems
- no failure of seals or weathertightness

At **MCE Mean** displacements:

- no dislodging of glass
- no other life safety risks


Notes:

\*Case 3 & 4 displacements are derived from taking SRSS of the two buildings.

"DBE" = Design Basis Earthquake

"MCE" = Maximum Considered Earthquake

# Low-Damage Skylight




Free Side

Fixed Side





# Low-Damage Glazing





# Low-Damage Stairs



# Design in the Shared Space Practice and Research



**The Salk Institute**

