

# Performance Based Economic Loss Assessment Due to a Hypothetical Large Southern California Earthquake Based on the Disruption and Recovery of Port of Los Angeles Freight Traffic

---



## Research Team

Barbaros Cetiner, UC Berkeley

Michael Virtucio, UC Berkeley

Bingyu Zhao, UC Berkeley

## Principal Investigators


Ertugrul Taciroglu, UC Los Angeles; Kenichi Soga, UC Berkeley

# Disaster Resilience


Under extreme events, the resilience of a transportation network is highly dependent on the performance of its physical components, such as roadways, bridges, and culverts.

Failure of some of these components, particularly bridges, could substantially disrupt the functioning of the network.

With the average bridge in the U.S. being 43 years old (ASCE, 2017), quantifying resiliency at network level requires detailed analyses of bridge seismic behavior.



# Objectives




Develop a methodology that generates high-resolution representations of post-disaster transportation network conditions, and the consequent economic losses

As a demonstration of the methodology, post-event performance the Greater Los Angeles transportation network will be investigated for a hypothetical large scenario earthquake affecting the Ports of Los Angeles and Long Beach.



Ports of Los Angeles and Long Beach

- Are the largest container terminals in the US
- Account for 40% US imports and 25% US exports


# Framework: Overview




# Framework: Hazard Characterization




(USGS, 2013)



(USGS, 2014)





(PEER, 2013)



(USGS, 2013)

# M 7.3 Palos Verdes Fault Scenario Earthquake







Magnitude: 7.3  
Epicentral distance: 2 mi (3.25 km)

# Framework: Assessment of Physical Damage

## Extract Bridge Geometry

Develop a 3D bridge model by coupling dimensions obtained from Google Street View images, bridge centerline derived from satellite images/OSM, ground elevation data



# Framework: Assessment of Physical Damage



## Extract Bridge Geometry

Develop a 3D bridge model by coupling dimensions obtained from Google Street View images, bridge centerline derived from satellite images/OSM, ground elevation data



## Model Bridges and Simulate Hazard Response




Model multiple realizations of the extracted bridge geometry using statistical distributions of structural properties, simulate their response to the determined loads



Transverse steel reinforcement ratio					
Distribution					
Design Era	Type	Mean	Standard Deviation	Lower Bound	Upper Bound
Pre-1971	#4 @ 12 in. irrespective of the cross-section				
Post-1971	Uniform	0.85	0.07	0.4	1.3




# Framework: Assessment of Physical Damage



# Bridges Modeled for This Project (1000)

---




# Traffic simulation: SCAG Road Network


Road network is downloaded from OpenStreetMap for the six counties that comprise the SCAG region (Imperial, Los Angeles, Orange, Riverside, San Bernardino, and Ventura).

The network consists of 615,714 intersections (nodes) and 1,444,790 roads (edges).


Post-earthquake bridge closures: {59, 44, 14, 10, 6} miles of roadway were closed {1, 3, 7, 14, 30} days after the earthquake



SCAG Road Network



Roads around Port of LA




Bridge closures

# Traffic Simulation: Travel Demand


Travel demand (origin-destination flow, OD) from SCAG were processed.

Left: A subset of the trips within the SCAG area: # totals trips considered = 10,680,134

Right: Trips from the ports to other destinations in the SCAG area. # trips = 200,000 ~ daily port traffic.




SCAG traffic: ~10.6 million trips



Port traffic: 0.2 million trips

# Methodology




Semi-dynamic traffic assignment model used to compute for traffic volume on roads before and after bridge closures.

Travel time update:

$$\hat{t} = t_0 \left( 1 + a \cdot \left( \frac{q}{q_{\max}} \right)^b \right)$$


- Vehicles are assumed to choose fastest path under current road closure and traffic congestion status.
- Trucks are restricted from using residential roads

# Impact measurements




# Unfulfilled trips

Number of Fulfilled Trips in Port Area




4% decrease

Unfulfilled trips a day after the earthquake (blue: overall; green: port)




# Travel time






# Vehicle hours traveled (VHT)



# Economic impact assessment



# Bridge closure costs versus bridge repair budgets

---

- 2022 California Bridge Formula Program budget: 575M USD (5-year program budget total: 4.2B USD; significantly below total repair cost estimated at 11.7B USD)
- Our study results: 1.56B USD direct cost and 768M USD indirect cost
  - estimated indirect cost (cost of externalities shouldered by individuals) post-earthquake shows that total costs increase by almost 50% without proper mitigation

# Discussion

---

- Port area is disproportionately impacted: accounts for 50% of all unfulfilled trips, 62% of total indirect cost
- Lost demand dominates indirect cost over delays; road network connectivity (particularly of port island to mainland LA) is key issue
- Almost 50% of post-earthquake impact costs can be avoided with proper mitigation
- Future work: include freight impacts more explicitly

# Thank you