



# Monitoring Bridge Performance Under Vehicle Loading with Dynamic Fiber Optic Strain Sensing

Rodrigo Tapia Corvalán ([rodrigo.tapia@berkeley.edu](mailto:rodrigo.tapia@berkeley.edu))

Matt DeJong ([dejong@berkeley.edu](mailto:dejong@berkeley.edu))

# Objectives


## Service load performance assessment of an RC bridge

- Collect and analyze strain data efficiently
- Characterize load distribution across the bridge structure
- Develop and validate computational models for performance analysis
- Evaluate long-term bridge monitoring using dynamic fiber optic strain sensing
- Post-earthquake damage evaluation





# Background

# Fiber optic strain sensing




(reference: Nicky De Battista  
<https://www.repository.cam.ac.uk/handle/1810/255405>)

# Crack measurement using fiber optic sensing



(Zhang et al., 2020)

# Crack measurement using fiber optic sensing



# Motivation

Evaluate use of fiber optics for quantifying real service loads and structural performance

# Centennial Viaduct



**VICINITY MAP**


SCALE: N.T.S.




**LOCATION MAP**

SCALE: N.T.S.

# FO sensing plan - deck




# FO sensing plan - deck





PLAN  
1" = 20'


# FO cables embedded in deck



# FO sensing plan - columns



# FO cables embedded in columns





# Data collection





# Example measurement



# Model consideration

- Shuttle Load:
  - Total weight  $\approx$  5.9 tons
  - Load per wheel
    - (in 2D, two wheels)  $\approx$  2,950 kg per wheel
  - Wheelbase  $\approx$  4.7 m
  - Track Width  $\approx$  2.2 m






(reference: UC Berkeley Bear Transit  
<https://pt.berkeley.edu/transportation-mobility/bear-transit>)

(reference: UC Berkeley Bear Transit  
<https://www.visitberkeley.com/directory/uc-berkeley-bear-transit/>)




# Model consideration




- Simple Linear Elastic Model for Initial Validation


- Cross-sectional Area:  $\approx 53.22 \text{ ft}^2 \approx 4.94 \text{ m}^2$
- Reinforced Concrete Properties:
  - Yield Strength ( $f_y$ ) = 60 ksi
  - Compressive Strength ( $f_{c'}$ ) = 3.6 ksi
  - Modulus of Elasticity ( $E$ )  $\approx 23,520 \text{ MPa}$




# Measurement: Longitudinal











Top cable:






Bottom cable:







# Measurement: Transversal

















Strain ( $\mu\epsilon$ )



PLAN









# Summary

- Collected and analyzed strain data efficiently
- Characterized load distribution across the bridge structure
- Developed an initial validation model for the strain data



# Future work

- Enhance computational modeling for improved accuracy
- Implement weight-in-motion (WIM) analysis
- Conduct long-term bridge performance monitoring
- Perform post-earthquake structural assessment

